

GTS 300 HPE-TECHNICAL SPECIFICATIONS

| ENGINE | 4-valve 4-stroke single cylinder, electronic injection, catalysed hpe |
|---------------------------------|--|
| DISPLACEMENT | 278 cc |
| BORE X STROKE | 75 mm x 63 mm |
| MAX POWER AT THE CRANK SHAFT | 17.5 kW - 23.8 HP - at 8,250 rpm |
| MAX TORQUE | 26 Nm at 5,250 rpm |
| CONSUMPTION | 31.2 km/l |
| CO2 EMISSIONS COMPLIANCE | 74 g/km |
| FUEL SYSTEM | Electronic Injection |
| COOLING | Liquid |
| STARTER | Electric |
| GEARBOX | CVT automatic with torque server |
| CLUTCH | Automatic dry centrifugal with shock absorbers |
| LOAD-BEARING STRUCTURE | Sheet steel shell with welded structural reinforcements |
| FRONT SUSPENSION | Single arm with helical spring and hydraulic shock absorber |
| REAR SUSPENSION | Double hydraulic shock absorber with helical spring with preload adjustable in 4 positions |
| FRONT BRAKE | Stainless steel Ø 220 mm disc with hydraulic control |
| REAR BRAKE | Stainless steel Ø 220 mm disc with hydraulic control |
| ABS/ASR SYSTEM | ABS/ASR standard |
| FRONT TYRE | Tubeless 120/70 - 12" |
| REAR TYRE | Tubeless 130/70 - 12" |
| LENGTH/WIDTH/WHEELBASE | 1,950 / 755 / 1,375 mm |
| SEAT HEIGHT | 790 mm |
| FUEL TANK CAPACITY | 8.5 litres |
| EMISSIONS COMPLIANCE | Euro 5 |